



4 SÄULEN HYDRAULISCHE ENTGRATPRESSEN HYDRAULIC 4 COLUMNS TRIMMING PRESSES

TECHNISCHE DATEN TECHNICAL SPECIFICATIONS			KZP 15/20	KZP 25	KZP 30/40	KZP 50/60	KZP 70/80
Presskraft / Pressing force		kN	150/200	250	300/400	500/600	700/800
Rückzugskraft / Return force		kN	23 / 30	35	34 / 45	50 / 60	75 / 85
Säulendurchgang Distance between columns	D x E	mm	620 x 420 620 x 620 - - 800 x 620 950 x 700 -	- 700 x 500 700 x 700 -	- 800 x 600 950 x 700 950 x 950 1000 x 1000 1100 x 1100 - 1200 x 1200 - 1250 x 1250 -	- 950 x 700 950 x 950 1000 x 1000 1100 x 1100 1200 x 800 1200 x 1200 1250 x 1000 2000 x 1100	- 1000 x 1000 1100 x 1100 - 1200 x 1200 -
Einbauhöhe / Distance between plates	A	mm	700→1000	800→1100	900→1500	900→1800	900→1800
Hub / Stroke	C	mm	400→800	500→900	500→1000	500→1300	500→1300
Aufspanntischhöhe / Table Highness	B	mm	900	900	900	900	900
Geschwindigkeit / Speed	Schliessen / Approach Arbeit / Working Öffnen / Return	mm/s	500	500	500	500	500
		mm/s	35	40	33	32	28
		mm/s	230	285	290	310	216
Motorleistung / Motor power		kW	7.5 / 9	11	11 / 15	18 / 22	22
Maschinengewicht / Machine weight	ca. / about	kg	2200	2500	4000	5500	7000